

## DECLARATION OF CONFORMITY



We hereby declare that the following product: Air Heater **EOLO B**, variants: **BL / BC** series of type:

BL 15,25,35,45,55,65,85,105, - AE / AC / AS

BL 120-150-200-250-300 - V / RT / AS interior version E / exterior version I

BC 15,25,35,45,55,65,85,105, - AE / AC / AS

produced in accordance to the following Europeans Directives

1. **2009/142/WE** – appliances burning fuels.
2. **2006/95/WE** – low-voltage electrical equipment.
3. **2004/108/WE** – electromagnetic compatibility,

and the following standards harmonized with the above directives:

**PN-EN 1020:2010** - Non-domestic forced convection gas-fired air heaters for space heating not exceeding a net heat input of 300 kW incorporating a fan to assist transportation of combustion air or combustion products.

**PN-EN 1196:2011** - Domestic and non-domestic gas-fired air heaters - Supplementary requirements for condensing air heaters.

**PN-EN 60335-1:2012E** – Household and similar electrical appliances - Safety -- Part 1: General requirements.

**PN-EN 60335-2-102:2006E+A1:2010E**

Household and similar electrical appliances - Safety -- Part 2-102: Particular requirements for gas, oil and solid-fuel burning appliances having electrical connections.

**PN-EN 55014-1:2007+ PN-EN 55014-1:2007/A1:2010 +PN-EN 55014-1:2007/A2:2011**

Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission.

**PN-EN 55014-2:1999+A1:2004+A2:2009**

Electromagnetic compatibility (EMC) -- Requirements for household appliances, electric tools and similar apparatus -- Immunity. Product family standard.

**PN-EN 61000-3-2:2007+A1:2010+A2:2010**


Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current  $\leq 16$  A per phase)

**PN-EN 61000-3-3:2011P**

Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current  $\leq 16$  A per phase and not subject to conditional connection.

Zduńska Wola, 2015.01.15

Product Manager  
Dariusz Przygocki



President  
Federico Cortelazzo

